







UniLine cassette at a glance



Details



Heat output



Dimensions




Unbeatable advantages

Controller models





























Fit into any ceiling grid

Do your plans include a suspended ceiling? Then opt for UniLine cassettes. They are hidden in the suspended ceiling and fit into a 600 mm or 625 mm ceiling grid.





















When it needs to be compact ...

... the simple connection is included: the unit and casing are a compact unit; the connections for electricity and water are lead out through the side of the unit. As a result, it can be installed close to the ceiling.





















For "yes-men"

Would you like lower investments? And high-performance? Then you simply should not deprive your customers of the UniLine cassettes.





















Step this way!

One step – and your customers are in a pleasant sales environment. Open doors reduce our reluctance to enter a shop – and besides, UniLine air screening reduces energy losses.





















Small shops and large malls

UniLine Cassettes effectively screen doors from cold air – with a height of up to 3 metres, individual or on a broad-scale.






















Maintenance-friendly and a pleasure to service

Make your service engineer your friend: virtually he entire underside of the unit acts as a service flap. The large filter and interior of the unit can be accessed in just a few simple steps.























UniLine cassettes at a glance







































































Controller models



KaControl room automation

- Factory-fitted KaControl technology to set up networked total systems based on a KaControl system
- Interfaces for BACnet* or Modbus building automation as an optional plug-in unit
- 0-10 V analog input to control the fan and valve via a single data point
- Room control unit design with intuitive user guidance
- ▶ Integrated timer programme

* Web server integrated

5-speed flush-mounted switch

- ➤ For installation in a 55 mm junction switch box
- ▶ Cover: white



5-speed surface-mounted switch

- In combination with a thermoelectric shut-off valve (accessories)
- In a plastic housing
- ▶ Light grey/dark grey























Technical Data

Size		10	15	20	25
Maximum discharge height ¹⁾	[m]	2,3 - 3,0	2,3 - 3,0	2,3 - 3,0	2,3 - 3,0
Maximum door width	[m]	1,0	1,5	2,0	2,5
Air flow volume ²⁾	[m³/h]	600 - 1390	930 - 2130	1210 - 2820	1660 - 4000
Heat output ³⁾	[kW]	6,7 - 10,2	9,6 - 17,4	13,1 - 24,2	18,0 - 33,9
Sound pressure level ⁴⁾	[dB(A)]	36 - 57	37 - 58	39 - 59	40 - 60

¹⁾ At good to average pressure ratios/requirements/conditions 2) Switchable in 5 stages 3) At LPHW 75/65 °C, t_{L1} = 20 °C 4) At a distance of 3 m























Dimensions





	UniLine Cassette					
Size	10	15	20	25		
Α	1035	1535	2035	2535		

All dimensions in mm

* also available for 600 mm ceiling grid





















Benefits for you!

Kampmann offers you the following service benefits:

- ▶ On-site Consultation
- Design Support
- ▶ After Sales Service

Here we are at your service: Kampmann.co.uk/contact























Kampmann.co.uk m.kampmann.co.uk



Kampmann GmbH
Friedrich-Ebert-Str. 128–130
49811 Lingen (Ems)
Germany

T + 49 591 7108-0

F + 49 591 7108-300

E info@kampmann.de

Kampmann UK Ltd.
Dial House, Govett Avenue
Shepperton, Middlesex, TW17 8A
Great Britain

T +44 (0)1932 228592

F +44 (0)1932 228949

E info@kampmann.co.uk





