

shape



Hudevad Plan XV



output table

HUDEVAD
shape

Radiator data Plan XV - length 550

| | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|-------------------------|----------------------|-----------------------|-----------------------|
| W/m 75°/65°/20°C | 1402 | 1739 | 2520 |
| W/m 55°/45°/20°C | 723 | 898 | 1300 |

Output in watts at a temperature set of 90° / 70° / 20°

| Height | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|-------------|----------------------|-----------------------|-----------------------|
| 1600 | 1375 | 1739 | 2507 |
| 1700 | 1439 | 1819 | 2629 |
| 1800 | 1494 | 1887 | 2731 |
| 1900 | 1693 | 2102 | 3039 |
| 2000 | 1757 | 2180 | 3158 |
| 2100 | 1801 | 2236 | 3242 |
| 2200 | 1851 | 2302 | 3340 |
| 2300 | 1838 | 2308 | 3338 |
| 2400 | 1885 | 2369 | 3429 |
| 2500 | 1931 | 2429 | 3516 |
| 2600 | 1918 | 2437 | 3517 |
| 2700 | 1968 | 2499 | 3610 |
| 2800 | 2024 | 2569 | 3715 |
| 2900 | 2247 | 2795 | 4056 |
| 3000 | 2252 | 2822 | 4085 |

Radiator data Plan XV - length 650

| | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|------------------|----------------------|-----------------------|-----------------------|
| W/m 75°/65°/20°C | 1752 | 2174 | 3150 |
| W/m 55°/45°/20°C | 904 | 1122 | 1626 |

Output in watts at a temperature set of 90° / 70° / 20°

| Height | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|--------|----------------------|-----------------------|-----------------------|
| 1600 | 1719 | 2174 | 3134 |
| 1700 | 1799 | 2274 | 3287 |
| 1800 | 1868 | 2359 | 3413 |
| 1900 | 2117 | 2628 | 3799 |
| 2000 | 2196 | 2725 | 3947 |
| 2100 | 2251 | 2795 | 4052 |
| 2200 | 2314 | 2877 | 4175 |
| 2300 | 2297 | 2885 | 4172 |
| 2400 | 2356 | 2961 | 4286 |
| 2500 | 2413 | 3037 | 4395 |
| 2600 | 2398 | 3046 | 4397 |
| 2700 | 2460 | 3124 | 4513 |
| 2800 | 2530 | 3211 | 4644 |
| 2900 | 2809 | 3494 | 5070 |
| 3000 | 2815 | 3527 | 5106 |

Radiator data Plan XV - length 750

| | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|------------------|----------------------|-----------------------|-----------------------|
| W/m 75°/65°/20°C | 2103 | 2609 | 3780 |
| W/m 55°/45°/20°C | 1085 | 1346 | 1951 |

Output in watts at a temperature set of 90° / 70° / 20°

| Height | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|--------|----------------------|-----------------------|-----------------------|
| 1600 | 2063 | 2608 | 3761 |
| 1700 | 2159 | 2729 | 3944 |
| 1800 | 2241 | 2830 | 4096 |
| 1900 | 2540 | 3153 | 4559 |
| 2000 | 2635 | 3269 | 4737 |
| 2100 | 2701 | 3354 | 4863 |
| 2200 | 2777 | 3453 | 5010 |
| 2300 | 2757 | 3462 | 5007 |
| 2400 | 2828 | 3553 | 5143 |
| 2500 | 2896 | 3644 | 5274 |
| 2600 | 2877 | 3656 | 5276 |
| 2700 | 2952 | 3749 | 5415 |
| 2800 | 3037 | 3853 | 5573 |
| 2900 | 3371 | 4192 | 6084 |
| 3000 | 3378 | 4232 | 6127 |

Radiator data Plan XV - length 850

| | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|------------------|----------------------|-----------------------|-----------------------|
| W/m 75°/65°/20°C | 2453 | 3044 | 4410 |
| W/m 55°/45°/20°C | 1266 | 1571 | 2276 |

Output in watts at a temperature set of 90° / 70° / 20°

| Height | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|--------|----------------------|-----------------------|-----------------------|
| 1600 | 2406 | 3043 | 4388 |
| 1700 | 2519 | 3184 | 4602 |
| 1800 | 2615 | 3302 | 4778 |
| 1900 | 2963 | 3679 | 5319 |
| 2000 | 3074 | 3814 | 5526 |
| 2100 | 3151 | 3914 | 5673 |
| 2200 | 3240 | 4028 | 5845 |
| 2300 | 3216 | 4039 | 5841 |
| 2400 | 3299 | 4145 | 6001 |
| 2500 | 3378 | 4251 | 6153 |
| 2600 | 3357 | 4265 | 6155 |
| 2700 | 3444 | 4373 | 6318 |
| 2800 | 3543 | 4495 | 6502 |
| 2900 | 3932 | 4891 | 7098 |
| 3000 | 3940 | 4938 | 7148 |

Radiator data Plan XV - length 950

| | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|------------------|----------------------|-----------------------|-----------------------|
| W/m 75°/65°/20°C | 2804 | 3479 | 5040 |
| W/m 55°/45°/20°C | 1447 | 1795 | 2601 |

Output in watts at a temperature set of 90° / 70° / 20°

| Height | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|--------|----------------------|-----------------------|-----------------------|
| 1600 | 2750 | 3478 | 5015 |
| 1700 | 2879 | 3638 | 5259 |
| 1800 | 2989 | 3774 | 5461 |
| 1900 | 3386 | 4204 | 6079 |
| 2000 | 3513 | 4359 | 6316 |
| 2100 | 3601 | 4473 | 6484 |
| 2200 | 3703 | 4604 | 6680 |
| 2300 | 3676 | 4616 | 6676 |
| 2400 | 3770 | 4738 | 6858 |
| 2500 | 3861 | 4858 | 7032 |
| 2600 | 3836 | 4874 | 7035 |
| 2700 | 3936 | 4998 | 7220 |
| 2800 | 4049 | 5137 | 7431 |
| 2900 | 4494 | 5590 | 8112 |
| 3000 | 4503 | 5643 | 8170 |

Radiator data Plan XV - length 1050

| | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|-------------------------|----------------------|-----------------------|-----------------------|
| W/m 75°/65°/20°C | 3154 | 3913 | 5670 |
| W/m 55°/45°/20°C | 1628 | 2020 | 2926 |

Output in watts at a temperature set of 90° / 70° / 20°

| Height | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|-------------|----------------------|-----------------------|-----------------------|
| 1600 | 3094 | 3913 | 5642 |
| 1700 | 3239 | 4093 | 5916 |
| 1800 | 3362 | 4245 | 6144 |
| 1900 | 3810 | 4730 | 6838 |
| 2000 | 3953 | 4904 | 7105 |
| 2100 | 4051 | 5032 | 7294 |
| 2200 | 4166 | 5179 | 7515 |
| 2300 | 4135 | 5193 | 7510 |
| 2400 | 4242 | 5330 | 7715 |
| 2500 | 4344 | 5466 | 7911 |
| 2600 | 4316 | 5484 | 7914 |
| 2700 | 4428 | 5623 | 8123 |
| 2800 | 4555 | 5779 | 8360 |
| 2900 | 5056 | 6289 | 9126 |
| 3000 | 5066 | 6348 | 9191 |

Radiator data Plan XV - length 1150

| | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|------------------|----------------------|-----------------------|-----------------------|
| W/m 75°/65°/20°C | 3505 | 4348 | 6300 |
| W/m 55°/45°/20°C | 1809 | 2244 | 3251 |

Output in watts at a temperature set of 90° / 70° / 20°

| Height | Depth = 86 (type 21) | Depth = 116 (type 22) | Depth = 173 (type 33) |
|--------|----------------------|-----------------------|-----------------------|
| 1600 | 3438 | 4347 | 6268 |
| 1700 | 3599 | 4548 | 6574 |
| 1800 | 3736 | 4717 | 6826 |
| 1900 | 4233 | 5255 | 7598 |
| 2000 | 4392 | 5449 | 7895 |
| 2100 | 4502 | 5591 | 8105 |
| 2200 | 4628 | 5755 | 8350 |
| 2300 | 4595 | 5770 | 8345 |
| 2400 | 4713 | 5922 | 8572 |
| 2500 | 4826 | 6073 | 8791 |
| 2600 | 4796 | 6093 | 8793 |
| 2700 | 4920 | 6248 | 9025 |
| 2800 | 5061 | 6421 | 9288 |
| 2900 | 5618 | 6987 | 10140 |
| 3000 | 5629 | 7054 | 10212 |